






# LUMINAIRES

## TRADITIONAL LIGHTING ORDERING GUIDE

MOUNTING BRACKETS					
Wall Mount	WM	Twin Head	TH	Multiple Head	Multiple Head OPTIONS
					<b>2 PT</b>  <b>4 PT</b> 

ELECTRICAL OPTIONS	CODE
Single Fused	<b>FS1</b>
Double Fused	<b>FS2</b>
Quick Disconnect	<b>QD</b>
Photoelectric Control	<b>PEC</b>

LENS OPTIONS	CODE
Acrylic Clear	<b>AC</b>
Acrylic Frosted	<b>AF</b>
Polycarbonate Clear	<b>PC</b>
Polycarbonate Frosted	<b>PF</b>
Tempered Glass	<b>TG</b>

VOLTAGE OPTIONS	CODE
120	<b>120</b>
208	<b>208</b>
240	<b>240</b>
480	<b>480</b>

OPTICAL OPTIONS					
REFRACTOR		CODE	REFLECTOR		CODE
Type III Borosilicate Glass Refractor		<b>RF3</b>	Type I Distribution		<b>T1</b>
Type V Borosilicate Glass Refractor		<b>RF5</b>	Type II Distribution		<b>T2</b>
Type V Multitiered Reflector		<b>LVR1</b>	Type III Distribution		<b>T3</b>
Houseside Shield 90°		<b>HSS</b>	Type IV Distribution		<b>T4</b>
			Type V Distribution		<b>T5</b>

LAMP HOLDER	
	CODE
Medium Base	<b>D</b>
Mogul Base	<b>G</b>

LIGH SOURCE AND WATTAGE OPTIONS			
	CODE		CODE
50 MH	<b>05H</b>	35 HPS	<b>03S</b>
70 MH	<b>07H</b>	50 HPS	<b>05S</b>
100 MH	<b>10H</b>	70 HPS	<b>07S</b>
150 MH	<b>15H</b>	100 HPS	<b>10S</b>
175 MH	<b>17H</b>	150 HPS	<b>15S</b>
250 MH	<b>25H</b>	250 HPS	<b>25S</b>

COLOR CODE											
Textured Black	<b>BKTX</b>	Satin Black	<b>BKST</b>	White	<b>WH</b>	Bronze	<b>BH</b>	Grey	<b>GY</b>	Hartford Green	<b>GNHF</b>

ORDERING NUMBER							
Luminaire, Light Source / Voltage & Wattage	Lamp Holder Type	Optical Option	Lens Option	Electrical Option	Arm Bracket Option	Color Option	
<b>LN13 17H</b>	<b>/ 120</b>	<b>/ D</b>	<b>/ T3</b>	<b>/ PC</b>	<b>/ FS1</b>	<b>/ 2PT-ST10</b>	<b>/ BKST</b>

This represents a LUM1300 with a 175 watt metal halide 120 volt ballast; medium base, with a type III distribution reflector; Clear polycarbonate lens, single fuse with a twin array mounted on a SET100 arm Bracket.

